



Hengshui City,  
Hebei Province, China



Mobile: +86-15030811699  
(WhatsApp, WeChat, Skype, Viber)



snow@snowate.com



www.snowate.com



Brine tanks are made of PE materials, featuring good toughness, easy to clean, economical and durable, good resistant to heat and frozen, easy to install and move. The brine tank is filled with softening salt to regenerate saturated ion exchange resins in the softener tanks. You may choose the right brine tank from the following aspects.

## Capacity

- Round (rational molding)

60 L	100 L	145 L	200 L	350 L	500 L
750 L	1000 L	1500 L	2000 L	3000 L	

- Square (blow molding)

70 L	100 L
------	-------

## Selection Reference Table

Your choice:

Brine Tank Model	Amount of Renewable Resin	Maximum Resin Tank Capacity	Salt Valve
YX-70	45 L	1054	<ul style="list-style-type: none"> <li>F1600</li> <li>F434/F434W (provided with a water filling protection device.)</li> </ul>
YX-100	65 L	1252	
YX-145	100 L	1465	
YX-200	135 L	1665	
YX-350	255 L	2162	<ul style="list-style-type: none"> <li>F1700</li> <li>F454 (provided with a water filling protection device.)</li> </ul>
YX-500	365 L	3065	
YX-750	530 L	3072	
YX-1000	730 L	3672	
YX-1500	1090 L	4872	
YX-2000	1445 L	6079	
YX-3000	2170 L	8079	

\*Brine tank capacity ≥ resin tank capacity

## Color

Gray	Blue
<i>Others</i>	

## Related Products

- Softening salt
- Multiport control valve
- Liquid level switch
- Salt valve
- Others*

## Related Applications

- Softening
- Others*